

9700

PASSIVE DEPOLARIZER

IQS-9700

R&D AND MANUFACTURER



- Two versions available: 1310 nm \pm 20/1550 nm \pm 20 nm and 1520 nm to 1620 nm
- Typical insertion loss of 3 dB at 1310 nm/1550 nm
- Typical degree of polarization (DOP) for LEDs: 3 % over 0.1 nm bandwidth
- Typical DOP of 10 % with the EXFO's 2600 series of Tunable Laser Sources

The IQS-9700 can virtually depolarize any low- and medium-coherence source such as high-power LEDs (SLDs), Fabry-Perot laser diodes, DFBs, as well as the EXFO IQS-2600 and FLS-2600 families of erbium-doped tunable laser sources.

Increase Measurement Reliability and Consistency

When testing amplifiers or when using a tunable laser source for characterizing WDM devices, the IQS-9700 is an excellent alternative to polarization scrambling techniques to obtain better repeatability and consistency over several measurements.

Innovative Design

EXFO is introducing a novel technique to obtain passive depolarization through a design made of singlemode optical fibers. The IQS-9700 typically reduces the degree of polarization (DOP) of EXFO's 2600 series of Tunable Laser Sources to 10 %.

The Passive Depolarizer, available as a stand-alone unit or as a one-slot module in the IQS-500 Intelligent Test System, is also part of the IQ-12003 Environmental Test System and is optional in the IQS-12004B DWDM Passive Component Test System.

SPECIFICATIONS^{1, 2}

Models	IQS-9723	IQS-9734
Operating wavelength (nm)	1310 ± 20/1550 ± 20	1520 to 1620
Fiber type	SMF-28	SMF-28
Insertion loss (dB) ³	3	3
Degree of polarization (%)	10 to 15	10 to 15
PDL (dB)	0.1	0.1

ORDERING INFORMATION

IQS-97XX-XX

Wavelength

23 = 1310/1550 nm

34 = 1520 to 1620 nm

Connector

EI-EUI-28 = UPC/DIN 47256

EI-EUI-76 = UPC/HMS-10/AG

EI-EUI-89 = UPC/FC narrow key

EI-EUI-90 = UPC/ST

EI-EUI-91 = UPC/SC

EI-EUI-95 = UPC/E-2000

EA-EUI-28 = APC/DIN 47256

EA-EUI-89 = APC/FC narrow key

EA-EUI-91 = APC/SC

EA-EUI-95 = APC/E-2000

Notes

- All specifications are typical values.
- Tested with IQS-2600 Tunable Laser Source at 1550 nm.
- Insertion loss per module, excluding connectors.



Corporate Headquarters > 400 Godin Avenue, Vanier (Quebec) G1M 2K2 CANADA | Tel.: 1 418 683-0211 | Fax: 1 418 683-2170 | info@exfo.com

Toll-free: 1 800 663-3936 (USA and Canada) | www.exfo.com

EXFO America	4275 Kellway Circle, Suite 122	Addison, TX 75001 USA	Tel.: 1 800 663-3936	Fax: 1 972 836-0164
EXFO Europe	Le Dynasteur, 10/12 rue Andras Beck	92366 Meudon la Forêt Cedex FRANCE	Tel.: +33.1.40.83.85.85	Fax: +33.1.40.83.04.42
EXFO Asia-Pacific	151 Chin Swee Road, #03-29 Manhattan House	SINGAPORE 169876	Tel.: +65 6333 8241	Fax: +65 6333 8242
EXFO China	Beijing New Century Hotel Office Tower, Room 1754-1755 No. 6 Southern Capital Gym Road	Beijing 100044 P. R. CHINA	Tel.: +86 (10) 6849 2738	Fax: +86 (10) 6849 2662

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. **Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.** For the most recent version of this spec sheet, please go to the EXFO website at <http://www.exfo.com/specs>. In case of discrepancy, the Web version takes precedence over any printed literature.