

RTUe-9120 external optical switch

HIGH-DENSITY 1XN MEMS-TYPE OPTICAL SWITCH UNIT

- Highest optical-switch-port density for OTDR-based remote fiber test systems and fiber monitoring applications.



KEY FEATURES

- Reliable 1XN MEMs optical switch
- MPO 16-fiber connectors
- Available in 32, 64, 128 and 256 ports
- Small footprint – 1/2U
- High port density, up to 512 ports/1U
- Low insertion loss for such a high port count
- Lifetime of over 2.5 billion cycles
- Very low power consumption

APPLICATIONS

- PON/FTTx central remote testing and monitoring
- Large- or edge-site fiber testing and surveillance
- Data-center interconnect and campus monitoring with large cable fiber counts

COMPATIBLE PRODUCTS



OTDR based remote test unit
RTU-2



Test access module (TAM) kit

OPTICAL SPECIFICATIONS

Parameter	Min.	Typical	Max.
Insertion loss ^a —All models at 1310, 1550 and 1650 nm (dB)		2	
Crosstalk ^b (dB)	50		-50
Back reflection ^b (dB)			-45
Switching time (ms)			300
Durability (cycles)		2.5 billion	
Fiber type		9/125 µm singlemode fiber	
Connector type	Output	MPO-APC (16 fibers populated onto a standard MPO 24 fibers ferrule)	
	Input	SC-APC	

ELECTRICAL SPECIFICATIONS

Latching type	Non-latching
Supply type	USB 2.0
Operating power consumption	~1 W

GENERAL SPECIFICATIONS

Chassis size	½ U, rackmount chassis (19")
Size (H x W x D)	22 mm x 440 mm x 220 mm (7/8 in x 17 5/16 in x 8 11/16 in)
Weight	1.2 kg (2.6 lb)
Temperature	Operating ^c Storage ^d
	-5 °C to 50 °C (23 °F to 122 °F) -40 °C to 70 °C (-40 °F to 158 °F)
Optical connector location	Front panel
Accessories included	
<ul style="list-style-type: none"> • Instruction manual (hard copy) • GP-3120: 1U rackmount brackets (kit of 2) • Extender brackets to ETSI rack size • 1.5 m optical jumper SC-APC to SC-APC with FLEX boots • USB cable, 1.8 m, right-angle connector 	

a. Measured at 23 °C ± 5 °C, including input and output connectors.

b. Measured at 1550 nm.

c. With less than 80% relative humidity, non-condensing.

d. With less than 95% relative humidity, non-condensing.

ORDERING INFORMATION

RTUe-9120-SPLX-XX

Configuration

- 32 = 1 x 32 port optical switch
- 64 = 1 x 64 port optical switch
- 128 = 1 x 128 port optical switch
- 256 = 1 x 256 port optical switch

Example: RTUe-9120-SPLX-32

EXFO headquarters T +1 418 683-0211 **Toll-free** +1 800 663-3936 (USA and Canada)

EXFO serves over 2000 customers in more than 100 countries. To find your local office contact details, please go to www.EXFO.com/contact.

For the most recent patent marking information, please visit www.EXFO.com/patent. EXFO is certified ISO 9001 and attests to the quality of these products. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. **Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.**

For the most recent version of this spec sheet, please go to www.EXFO.com/specs.

In case of discrepancy, the web version takes precedence over any printed literature.